

# Absolute

Water-based, odourless, decorative paint with extra-matt natural finish and high chromatic depth. Highly breathable, it is ideal for completing dehumidifying systems. Italian design for living comfort.

Thanks to its high concentration of pigments, oils and active principles, Absolute is a rich paint characterized by an elegant texture that recalls the style of natural lime-based paints. Available in the 10 Warm Collection colours.



## Rating 4\*

- × VOC Low Emission
- ✓ Water based
- ✓ Solvent  $\leq 80$  g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

\* Rating based on average colour formulations

1. High breathability
2. Extra-matt
3. Excellent coverage
4. No splash
5. Free from heavy metals according to EN 71-3 standard, ideal for children's bedrooms
6. VOC-free, does not release harmful substances for human health and the environment
7. Does not produce odours
8. F+ Fungistatic
9. B+ Bacteriostatic
10. Free from Formaldehyde

---

## Areas of application

- Decorative and protective paint
- Intended use:
  - Interior walls and ceilings on:
    - traditional plaster
    - ready mixed plaster
    - dehumidifying plasters
    - prefabricated cement elements
    - gypsum based plaster and plasterboard
    - cement or gypsum based finish plasters
    - old paint layers and coatings in good condition and well anchored to the substrate.

**Do not use**  
On substrates which are dirty, non-cohesive, powdery.  
In walls with rising damp without a suitable dehumidifying system.

---

## Instructions for use

- Preparation of substrates
  - Carefully clean the substrates using suitable equipment to remove all traces of dirt, dust or efflorescences.
  - Completely remove any loose debris or parts that do not fully adhere to the substrate from deteriorated paint coatings and coverings.
  - New render patch layers must be left to cure until the bonding agent has set and primed with Universal Wall Primer; wait for 6 hours before the subsequent paint cycle. On plasters or inconsistent and loose finishing coats, apply Universal Wall Primer. On smooth and compact finishing coats, apply Universal Wall Primer.
  - In the presence of mould or biodeteriorating agents, repair first with Kerakover Activ.

- Preparation
  - Mix the product before application.

- Application
  - Using a brush, roller or spray, carefully apply across the entire surface two coats of Absolute either pure or diluted with water by up to 5-10% of the total volume depending on requirements and the tools used; on substrates which are perfectly dry or with a humidity level not greater than 6%.
  - Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and a relative ambient humidity lower than 80%.
  - Leave at least 6 hours between the first and second coats at 23 °C and R.H. of ≤ 80%.
  - If different batches of product are used, it is suggested to mix different buckets together in order to avoid slight differences in tone.

- Cleaning
  - Product residues can be removed with running water before the product has hardened.

---

## Special notes

- Evaluate seasonal application conditions: different temperature and humidity conditions result in significant differences in paint drying and/or reaction times.
- The photographic images in the catalogue and on the website, as well as the colours shown in the samples are to be considered purely indicative.
- Use material from a single production batch for each project.
- Materials from different batches may have slight colour and sheen variations.

## Certificates and marks



\* Émission dans l'air intérieur Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

## Abstract

*Protection and decoration of internal walls and ceilings: made by applying by brush, roller or spray, two coats of a paint, such as Absolute by Kerakoll Spa, GreenBuilding Rating® 4, with a coverage of  $\approx 0.15-0.2$  l/m<sup>2</sup>. Highly breathable, VOC-free, free from heavy metals according to EN 71-3 standard, fungistatic and bacteriostatic. Resistance to wet scrubbing (ISO 11998) > class 2 EN 13300, with permeability to water vapour class V1 (high) according to EN ISO 7783-2 standard.*

### Technical Data compliant with Kerakoll Quality Standard

Appearance	white or coloured paint
Volumetric mass	$\approx 1.3$ kg/l
Chemical nature	synthetic resins
Pack	buckets 4 – 10 l
Shelf life:	$\approx 12$ months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Humidity of the substrate	$\leq 6\%$
Waiting time between 1 <sup>st</sup> and 2 <sup>nd</sup> coat	$\geq 6$ hrs
Coverage when applying two coats for a fine-texture, two-coat finish	$\approx 0.15 - 0.20$ l/m <sup>2</sup>

Average values taken on Kerakoll Warm Collection colours at a temperature of +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site: temperature, ventilation and absorbency level of the substrate

**Performance****HIGH-Tech**

Resistance to wet scrubbing (ISO 11998)	> class 2	EN 13300
Permeability to water vapour (ISO7783)	Sd 0.01 m; class V1 (high)	ISO1062-1
Coverage (referred to white colour) (ISO6504-3)	class 1, 99.5% coverage with 6.2 m <sup>2</sup> /l consumption	ISO 13007-4.1.4
Gloss (very opaque) (ISO2813)	< 3 gloss at 85°	EN 13300

Average values taken on Kerakoll Warm Collection colours at a temperature of +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

## Warning

- Product for professional use
- abide by any standards and national regulations
- if necessary, ask for the safety data sheet

- for any other issues, contact the Kerakoll  
Worldwide Global Service +39 0536 811 516 -  
globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating® Manual 2012. This information was last updated in January 2021 (ref. GBR Data Report - 02.21); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.

Dreamed by

Kerakoll Spa  
via dell'Artigianato 9  
41049 Sassuolo - MO

Info

+39 0536.816.511  
info@kerakoll.com

Go green

Green Building  
Experience on  
[www.kerakoll.com](http://www.kerakoll.com)