

Clean and Seal

Detergent for building sites finishes. Rapid drying, degreasing detergent for the preparation of substrates, smoothing of joints and post-installation cleaning.



1. Free form residues and greasy films
2. It safeguards substrates
3. Rapid action and drying

Areas of application

→ Rapid-drying, degreasing detergent for substrates. Multi-purpose and fast-acting. Compatible with most substrates: PVC, plexiglass, aluminium and metal, tiles and ceramic tiles, glass and mirrors, natural stones, cement.

Eases the smoothing of joints for a perfect finish while saving time.
Post-installation detergent for the removal of stains, adhesive, PU hybrid mastic or silicone (non-hardened) residues, traces of adhesives and labels.

Instructions for use

→ Shake the canister before use. Spray keeping the canister at 20 cm from the surfaces to be cleaned. Dry with a cloth.

Allow to evaporate completely before performing any bonding or sealing.

Certificates and marks



Technical Data compliant with Kerakoll Quality Standard

Colour	colourless
Odour	hydrocarbon
Volumetric mass at +20 °C	780 kg/m ³
Flash point VC	< 0 °C
Shelf life	≈ 24 months
Pack	canister with a rated capacity of 650 ml - net volume 400 ml CO ₂ propeller gas - 12 pieces per carton/pack

Warning

→ Product for professional use
→ store the canisters in vertical position in a dry and cool place, away from sunlight
→ See the product safety data sheet

→ for any other issues, contact the Kerakoll Worldwide Global Service +33 (0) 4 72 89 06 80 - globalservice@kerakoll.com

The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in June 2024 (ref. GBR Data Report - 06.24); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.