

# Diluyente 01

**Eco-friendly thinner to thin alcohol-based and neoprene organic adhesives, ideal for use in GreenBuilding. Single-component with no environmental hazard rating.**

Diluyente 01 is a mixture of pure solvents which increase the workability and open time of alcohol-based and neoprene adhesives to lay resilient materials and carpeting. Specifically intended to remove adhesive residues and clean equipment.



**GREENBUILDING RATING®**

Low Emission  
IAQ  
Indoor Air Quality

Water Based

SLV  
REDUCED  
Solvent ≤ 90 g/l kg

Low Ecological Impact

Health Care

No environmental hazard rating

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

**PRODUCT STRENGTHS**

- High level of purity and compatibility with alcohol-based and neoprene adhesives
- Effectively removes any adhesive residues

**AREAS OF USE**

**Use**  
Dilution of solvent adhesives and cleaning of residues of adhesives or paint coatings from tools.

Specifically intended for the dilution of the following products:

- S45 Extra
- S45
- S45 F

**Do not use**  
For diluting water and solvent based paints, primer and waterproofing products, single and two-component reactive adhesives, adhesives dispersed in water.

**INSTRUCTIONS FOR USE**

Add up to a maximum of 5% to the products indicated above, following the instructions on the relevant technical data sheets. Remove product residues from the tools and clean with a cloth soaked in Diluyente 01. Leave the tools to soak in Diluyente 01 if necessary. Carefully dry the tools from the residues of Diluyente 01 before using.

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	transparent liquid
Chemical base	organic solvents
Pack	10 l drums
Shelf life	≈ 24 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +35 °C
Boiling point	+110 °C
Flash point	-5 °C
Density at +20 °C	0.85 g/cm <sup>3</sup>

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbcency level of the substrate.

## WARNING

- **Product for professional use**
- abide by any standards and national regulations
- respect the dilution ratios suggested in this data sheets and in the data sheet mentioned above
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in November 2019 (ref. GBR Data Report - 12.19); please note that additions and/or amendments may be made over time by KERAKOLL SpA, for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)