

# Diluyente Oil

Eco-friendly thinner for oil-based and oil-urethane varnishes and waxes.

Diluyente Oil is a mixture of solvents developed for Oil-Pur which guarantees increased fluidity and penetration. Specifically intended to remove residues and clean equipment.



**SLC**  
TECHNOLOGY



## Rating 1

1. High level of purity
2. High solvent power mix that is highly compatible with oil and oil-urethane based products

- × VOC Low Emission
- × Water Based
- × Solvent  $\leq$  80 g/kg
- ✓ Low Ecological Impact
- × Health Care

---

## Areas of application

→ Intended use:

Specifically intended for diluting:

- Oil-Pur, Silocera
- waxes and solvents
- pickling, removal of stains and residues on wood floors treated with wax

Interior wood floors in residential buildings.

Do not use for the dilution of solvent and water based, base coat and top coat varnish, primer and waterproofing products, adhesives in general.

---

## Instructions for use

→ Preparation

The product is ready-to-use.

→ Application

- For the dilution of Oil-Pur and Silocera add 5 – 10 % of Diluente Oil according to need and the instructions on the product technical data sheets.

- For pickling and the removal of stains and old layers of wax, and when necessary on untreated wood, rub the floor surface with a clean cloth soaked in Diluente Oil.
- For cleaning and removing remains of product from tools, clean with a cloth soaked in Diluente Oil. If necessary, leave the tools to soak in Diluente Oil, dry the tools with care before use.

---

### Technical Data compliant with Kerakoll Quality Standard

Appearance	dark brown liquid
Pack	oilers 5 l
Shelf life	≈ 24 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +35 °C
Boiling point	+146 °C
Flash point	+36 °C
Density at +20 °C	0.79 g/cm <sup>3</sup>

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbcency level of the substrate.

---

# Warning

- Product for professional use
- abide by any standards and national regulations
- respect the dilution ratios suggested in this data sheets and in the data sheet mentioned above
- respect the suggested dilution ratios and do not apply excessive amounts of product
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service - [info@kerakoll.ae](mailto:info@kerakoll.ae)

The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in June 2023 (ref. GBR Data Report - 06.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.