

## kerakoll

## **DECLARATION OF PERFORMANCE No 0442**

- 1. Unique identification code of the product-type: H40 GEL
- 2. Intended use/es: Improved cementitious adhesive for all internal and external tiling
- 3. Manufacturer: Kerakoll UK Ltd Tomlinson Road, Leyland, Lancashire, PR25 2DY,
- 4. System/s of AVCP:

System 3

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

Istituto Giordano No. 0407

6. Declared performance/s:

| Essential characteristics                          | Performance    |
|--|----------------|
| Reaction to fire                                   | Class A2-s1,d0 |
| Bond strength as:                                  |                |
| initial tensile adhesion strength                  | ≥ 1,0 N/mm²    |
| Durability for:                                    |                |
| Tensile adhesion strength after heat ageing        | ≥ 1,0 N/mm²    |
| Tensile adhesion strength after water immersion    | ≥ 1,0 N/mm²    |
| Tensile adhesion strength after freeze-thaw cycles | ≥ 1,0 N/mm²    |
| Release of dangerous substances                    | See SDS        |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Carl Gardner (Regional Managing

## Director)

At Leyland, on 01/06/2024

Kerakoll UK Ltd Tomlinson Road, Leyland, PR25 2DY United Kingdom

+44 (0) 1772 456 831 info@kerakoll.co.uk www.kerakoll.com Co Reg. No: 04627336 VAT number GB 636237732