



kerakoll

DECLARATION OF PERFORMANCE No 0632

1. Unique identification code of the product-type: **SETAFLEX RAPID**
2. Intended use/es: **Improved fast setting deformable cementitious adhesive with reduced slip for internal and external use**
3. Manufacturer: **Kerakoll UK Ltd - Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.**
4. System/s of AVCP:
System 3
5. Harmonised standard: **EN 12004:2007 + A1:2012**
Notified body/ies: **Modena centro prove No. 1599**
WFR Gent N.V. No. 1173
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1, d0
Bond strength as: early tensile adhesion strength initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$
Durability for: Tensile adhesion strength after heat ageing Tensile adhesion strength after water immersion Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Carl Gardner (Regional Managing Director)**

At Leyland, on 01/06/2024

Kerakoll UK Ltd
Tomlinson Road,
Leyland, PR25 2DY
United Kingdom

+44 (0) 1772 456 831
info@kerakoll.co.uk
www.kerakoll.com

CO Reg. No: 04021550
VAT number GB 636237732