

## kerakoll

## **DECLARATION OF PERFORMANCE No 0633**

- 1. Unique identification code of the product-type: SETAFLEX STANDARD
- 2. Intended use/es: Improved deformable cementitious adhesive with reduced slip for internal and external use
- 3. Manufacturer: Tilemaster Adhesives Ltd Kerakoll Group Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.
- 4. System/s of AVCP:

System 3

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

WFR Gent N.V. No. 1173

## 6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2,S1-d0
Bond strength as:	
initial tensile adhesion strength	≥ 1,0 N/mm²
Down by 1914 of Same	
Durability for:	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Filippo lacconi (General Manager)

At Leyland, on 27/11/2023

fairmfings