



DECLARATION OF PERFORMANCE No 0191

1. Unique identification code of the product-type: **GEOLITE 10**
2. Intended use/es: **Coating for surface protection of concrete structures according to principles 2 (MC), 5 (PR) and 8 (IR).**
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP: **System 2+ and System 4 for reaction to fire**
5. Harmonised standard: **EN 1504-2:2004**
Notified body/ies: **S.G.S. Italia No.1381**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Permeability to water vapour Capillary absorption and permeability to water Adhesion strength by pull-off test Linear shrinkage Coefficient of thermal expansion Abrasion resistance Resistance to thermal shock Impact resistance	Class I, $S_d < 5 \text{ m}$ $w < 0,1 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0,5}$ $\geq 2,0 \text{ N/mm}^2$ $\leq 0,3\%$ $\alpha_t \leq 30 \cdot 10^{-6} \text{ }^\circ\text{K}^{-1}$ weight loss $< 3000 \text{ mg}$ adhesion strength $\geq 2,0 \text{ N/mm}^2$ Class III
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**

At Castellón, on 03/02/2020



DECLARATION OF PERFORMANCE No 0191

1. Unique identification code of the product-type: **GEOLITE 10**
2. Intended use/es: **Product for concrete structural repair according to principles: 3 (CR), 4 (SS) and 7 (RP).**
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP: **System 2+ and System 4 for reaction to fire**
5. Harmonised standard: **EN 1504-3:2005**
Notified body/ies: **S.G.S. Italia No.1381**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R4
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 2,0 MPa
Thermal compatibility (freeze-thaw)	≥ 2,0 MPa
Capillary absorption	≤ 0,5 kg · m⁻² · h^{-0,5}
Elastic modulus CC	≥ 20 GPa
Elastic modulus PCC	≥ 20 GPa
Carbonation resistance	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**

At Castellón, on 03/02/2020

www.kerakoll.com

KERAKOLL IBÉRICA S.A. – Carretera de Alcora, km. 10,450 – 12006 Castellón de la Plana – España
Tel. +34 964 251 500 – Fax +34 964 241 100 – e-mail: info@kerakoll.es

C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.



DECLARATION OF PERFORMANCE No 0191

1. Unique identification code of the product-type: **GEOLITE 10**
2. Intended use/es: **Product for reinforcement corrosion protection according to principle 11 (CA).**
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP: **System 2+**
5. Harmonised standard: **EN 1504-7:2006**
Notified body/ies: **S.G.S. Italia No.1381**
6. Declared performance/s:

Essential characteristics	Performance
Shear adesion	Pass
Corrosion protection	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**

At Castellón, on 03/02/2020