



DECLARATION OF PERFORMANCE No 0494

1. Unique identification code of the product-type: **H40 GEL**
2. Intended use/es:
Improved cementitious adhesive for all internal and external tiling
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP:
System 3
System 3 for reaction to fire
5. Harmonised standard: **EN 12004:2007 + A1:2012**
Notified body/ies: **CEMOSA INGENIERA Y CONTROL N° 1377**
AIDIMME N° 1981
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1,d0
Bond strength as: initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for: Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**

At Castellón, on 15/07/2020