kerakoll

DECLARATION OF PERFORMANCE No 0552

- 1. Unique identification code of the product-type: NANOFLEX SIN LIMITES
- 2. Intended use/es:

Polymer modified cementitious liquid-applied (CM O1P) water impermeable product In external installation and in swimming pools, beneath ceramic tilling (bonded with C2 adhesive in accordance with EN 12004)

- 3. Manufacturer: Kerakoll Ibérica, S.A.U. Ctra. Alcora Km 10,450 Castellón España
- 4. System/s of AVCP:

System 3 for waterproofing System 4 for all the characteristics other than waterproofing

5. Harmonised standard: EN 14891:2012+AC:2012

Notified body/ies: Modena Centro Prove No.1599

6. Declared performance/s:

Essential characteristics	Performance
Initial tensile adhesion strength	≥0,5 N/mm²
Tensile adhesion strength after water contact	≥0,5 N/mm²
Tensile adhesion strength after heat ageing	≥0,5 N/mm²
Tensile adhesion strength after contact with lime water	≥0,5 N/mm²
Waterproofing	No penetration
Tensile adhesion strength after contact with chlorinated water	≥0,5 N/mm²
Crack bridging ability under standard conditions (+23°C)	≥0,75 mm
Crack bridging ability at low temperature (-5°C)	≥0,75 mm
Tensile adhesion strength after freeze-thaw cycles	≥0,5 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Pau Ramia (legal representative)

Castellón 08/05/2024

kerakoll.com

KERAKOLL IBÉRICA S.A.U. – Carretera de Alcora, km. 10,450 – 12006 Castellón de la Plana – España Tel. +34 964 251 500 – Fax +34 964 241 100 – e-mail: info@kerakoll.es

C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.