

kerakoll

DECLARATION OF PERFORMANCE NO. 0553

1. Unique identification code of the product-type: GEOCALCE F ANTISISMICO

2. Intended use/es: General purpose masonry mortar (G) in masonry walls, columns and partitions

3. Manufacturer: Kerakoll Ibérica, S.A. - Ctra. Alcora Km 10,450 Castellón - España

4. System/s of AVCP:

System 2+

System 4 for reaction to fire

Harmonised standard: EN 998-2:2016
Notified body/ies: LRQA Iberia No.0094

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	M 15
Shear bond strength	0,15 N/mm²(t.v.)
Flexural bond strength	NPD
Contents of chloride	≤ 0,05%
Water absorption	0,2 Kg/m²min ^{0,5}
Water vapour permeability	μ 15/35 (t.v.)
Thermal conductivity	0,82 W/mK (t.v.)
Durability (against freeze-thaw)	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Pau Ramia (legal representative)

At Castellón, on 05/03/2025





kerakoll

DECLARATION OF PERFORMANCE No 0553

1. Unique identification code of the product-type: GEOCALCE F ANTISISMICO

2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works

3. Manufacturer: Kerakoll Ibérica, S.A. - Ctra. Alcora Km 10,450 Castellón - España

4. System/s of AVCP:

System 2+

System 4 for reaction to fire

Harmonised standard: EN 1504-3:2005
Notified body/ies: LRQA Iberia No.0094

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	Class R1
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 0,8 MPa
Thermal compatibility (freeze-thaw)	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)** At Castellón, on 05/03/2025

