kerakoll

DECLARATION OF PERFORMANCE NO. 0554

- 1. Unique identification code of the product-type: GEOCALCE G ANTISISMICO
- 2. Intended use/es: General purpose masonry mortar (G) in masonry walls, columns and partitions
- 3. Manufacturer: Kerakoll Ibérica, S.A. Ctra. Alcora Km 10,450 Castellón España
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

- 5. Harmonised standard: EN 998-2:2016 Notified body/ies: LRQA Iberia No.0094
- 6. Declared performance/s:

| Essential characteristics | Performance |
|----------------------------------|-----------------------------|
| Reaction to fire | Class A1 |
| Compressive strength | M 15 |
| Shear bond strength | 0,15 N/mm²(t.v.) |
| Flexural bond strength | NPD |
| Contents of chloride | ≤ 0,05% |
| Water absorption | 0,3 Kg/m²min ^{0,5} |
| Water vapour permeability | μ 15/35 (t.v.) |
| Thermal conductivity | 0,82 W/mK (t.v.) |
| Durability (against freeze-thaw) | NPD |
| Release of dangerous substances | See SDS |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Pau Ramia (legal representative)

At Castellón, on 03/02/2025

kerakoll.com

KERAKOLL IBÉRICA S.A. - Carretera de Alcora, km. 10,450 - 12006 Castellón de la Plana - España Tel. +34 964 251 500 - Fax +34 964 241 100 - e-mail: info@kerakoll.es

C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.

kerakoll

DECLARATION OF PERFORMANCE No 0554

- 1. Unique identification code of the product-type: GEOCALCE G ANTISISMICO
- 2. Intended use/es: Repair products for concrete, used in buildings and civil engineering works.
- 3. Manufacturer: Kerakoll Ibérica, S.A. Ctra. Alcora Km 10,450 Castellón España
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

5. Harmonised standard: EN 1504-3:2005

Notified body/ies: LRQA Iberia No.0094

6. Declared performance/s:

| Essential characteristics | Performance |
|-------------------------------------|-------------|
| Reaction to fire | Class A1 |
| Compressive strength | Class R1 |
| Chloride ion content | ≤ 0,05 % |
| Adhesive bond | ≥ 0,8 MPa |
| Thermal compatibility (freeze-thaw) | Pass |
| Release of dangerous substances | See SDS |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Pau Ramia (legal representative)

At Castellón, on 03/02/2025

kerakoll.com

KERAKOLL IBÉRICA S.A. – Carretera de Alcora, km. 10,450 – 12006 Castellón de la Plana – España Tel. +34 964 251 500 – Fax +34 964 241 100 – e-mail: info@kerakoll.es C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.