

kerakoll

DECLARATION OF PERFORMANCE No. 0555

- 1. Unique identification code of the product-type: GEOCALCE FL ANTISISMICO
- 2. Intended use/es: General purpose masonry mortar (G) in masonry walls, columns and partitions
- 3. Manufacturer: Kerakoll Ibérica, S.A. Ctra. Alcora Km 10,450 Castellón España
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

Harmonised standard: EN 998-2:2016
Notified body/ies: S.G.S. Italy No.1381

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	M 15
Shear bond strength	0,15 N/mm² (t.v.)
Flexural bond strength	NPD
Contents of chloride	≤ 0,05%
Water absorption	0,6 Kg/m²min ^{0,5}
Water vapour permeability	μ 15/35 (t.v.)
Thermal conductivity	0,82 W/mK (t.v.)
Durability (against freeze-thaw)	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Pau Ramia (legal representative)

At Castellón, on 06/06/2022

