



kerakoll

DECLARATION OF PERFORMANCE No 0569

1. Unique identification code of the product-type: **BIOCALCE BENESSERE**
2. Intended use/es: **Renovation mortar (R) : internal/external use.**
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP:
System 4
System 4 for reaction to fire
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies:-
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Adhesion Water absorption Water vapour diffusion coeff. Thermal conductivity (λ_{10}, dry) Durability (against freeze-thaw)	$\geq 0,1 \text{ N/mm}^2$ - FP:B $\geq 0,3 \text{ Kg/m}^2$ after 24 h $\mu 8$ $0,14 \text{ W/mK}$ NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia** (representante legal)

At Castellón, on 16/09/2022

kerakoll.com

KERAKOLL IBÉRICA S.A. – Carretera de Alcora, km. 10,450 – 12006 Castellón de la Plana – España
Tel. +34 964 251 500 – Fax +34 964 241 100 – e-mail: info@kerakoll.es

C.I.F. A-12331435. Inscrita en el Registro Mercantil de CASTELLÓN, TOMO 594, LIBRO 161, FOLIO 101, HOJA N.º CS 4393, INSC. I.ª SECC. G.



kerakoll

DECLARATION OF PERFORMANCE No 0569

1. Unique identification code of the product-type: **BIOCALCE BENESSERE**
2. Intended use/es: **Thermal insulating mortar (T) : internal/external use.**
3. Manufacturer: **Kerakoll Ibérica, S.A. – Ctra. Alcora Km 10,450 Castellón - España**
4. System/s of AVCP:
System 4
System 4 for reaction to fire
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies:-
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Adhesion	$\geq 0,1$ N/mm² - FP:B
Water absorption	W_c1
Water vapour diffusion coeff.	μ 8
Thermal conductivity (λ_{10}, dry)	0,14 W/mK (T₂)
Durability (against freeze-thaw)	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia** (representante legal)

At Castellón, on 16/09/2022

kerakoll.com

KERAKOLL IBÉRICA S.A. – Carretera de Alcora, km. 10,450 – 12006 Castellón de la Plana – España
Tel. +34 964 251 500 – Fax +34 964 241 100 – e-mail: info@kerakoll.es