

## kerakoll

## **DECLARATION OF PERFORMANCE No 0608**

- 1. Unique identification code of the product-type: PRAGMA FLEX
- 2. Intended use/es:

Improved cementitious adhesive for ceramic tiling, all internal and external tiling

- 3. Manufacturer: Kerakoll Ibérica, S.A. Ctra. Alcora Km 10,450 Castellón Spagna
- 4. System/s of AVCP:

System 3

System 3 for reaction to fire

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: CEMOSA INGENIERA Y CONTROL N° 1377

**AIDIMME N° 1981** 

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1/A1 <sub>fl</sub>
Bond strength as:	
initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for:	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Pau Ramia (legal representative)**At Castellón, on 11/07/2023

