



DECLARATION OF PERFORMANCE No. 0332

1. Unique identification code of the product-type: **FIXACRYL F PLUS**
2. Intended use/es: **Sealant for external and internal, non-structural use: facade joints.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:
System 3 and System 3 for reaction to fire
5. Harmonised standard: **EN 15651-1:2012**
Notified body/ies: **GINGER CEBTP, No. 0074**
Laboratoire National de metrologie et d'Essais, No. 0071
6. Declared performance/s:
EN15651-1 F-EXT-INT (class 12,5P)
Pretreatment: Method A
Substrate: aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 25%
Elongation after water immersion	≥ 100%
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 10/07/2017