



## **DECLARATION OF PERFORMANCE No. 0334**

1. Unique identification code of the product-type: RESYCOLLE ISO

2. Intended use/es: Sealant for external and internal, non-structural use: facade joints.; included cold climates.

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 4 for reaction to fire

5. Harmonised standard: EN 15651-1:2012

Notified body/ies: GINGER CEBTP, No. 0074

**6.** Declared performance/s:

EN15651-1 F-EXT-INT -CC (Class 25 HM)

Pretreatment: Method A

Substrate: aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class F
Resistance to flow Loss of volume Tensile properties at maintained extension after water immersion Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C) Durability	≤ 3 mm ≤ 10% Pass Pass Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 15/06/2017







## **DECLARATION OF PERFORMANCE No. 0334**

1. Unique identification code of the product-type: RESYCOLLE ISO

2. Intended use/es: Sealant for non-structural use: sanitary joints .

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 4 for reaction to fire

5. Harmonised standard: EN 15651-3:2012

Notified body/ies: GINGER CEBTP, No. 0074

**6.** Declared performance/s:

EN15651-3 S (Class XS3)

Pretreatment: Method A

Substrate: Aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class F
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20%
Tensile properties at maintained extension after immersion in water	Pass
Microbiological growth	4
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 15/06/2017







## **DECLARATION OF PERFORMANCE No. 0334**

1. Unique identification code of the product-type: RESYCOLLE ISO

2. Intended use/es: Sealant for movement joints in floors for interior and exterior application, for non-structural use; included cold climates.

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 4 for reaction to fire

5. Harmonised standard: EN 15651-4:2012

Notified body/ies: GINGER CEBTP, No. 0074

**6.** Declared performance/s:

EN15651-4 PW-EXT-INT-CC (Classe 12,5 E)

Pretreatment: Method A


Substrate: aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class F
Loss of volume	≤ 15%
Tensile properties at maintained extension	Pass
Adhesion / cohesion properties at maintained extension after water immersion	Pass
Adhesion / cohesion properties at maintained extension after salt water immersion	Pass
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30℃)	Pass
Tear resistance	Pass
Durability	Pass
Release of dangerous substances	Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 15/06/2017



www.kerakoll.com