



**DECLARATION OF PERFORMANCE No. 0337**

1. Unique identification code of the product-type: **RESYLSANIT**
2. Intended use/es: **Sealant for external and internal, non-structural use: facade joints; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN 15651-1:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
6. Declared performance/s:  
**EN15651-1 F-EXT-INT-CC (Class 25 LM)**  
**Pretreatment: Method A**  
**Substrate: glass; without primer**  
**aluminium without primer**  
**mortar M1 with primer**

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class E</b>
<b>Resistance to flow</b>	<b>≤3 mm</b>
<b>Loss of volume</b>	<b>≤10 %</b>
<b>Tensile properties at maintained extension after water immersion</b>	<b>Pass</b>
<b>Secant tensile modulus at -30°C</b>	<b>≤0,9 MPa</b>
<b>Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)</b>	<b>Pass</b>
<b>Durability</b>	<b>Pass</b>
<b>Release of dangerous substances</b>	<b>See SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 27/09/2019

**www.kerakoll.com**

KERAKOLL FRANCE au capital de € 6.500.000,00  
25 Avenue de l'Industrie - 69960 Corbas, France  
Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



## DECLARATION OF PERFORMANCE No. 0337

1. Unique identification code of the product-type: **RESYLSANIT**
2. Intended use/es: **Sealant used for sealing glazing applications; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN 15651-2:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
6. Declared performance/s:  
**EN15651-2 G-CC (Class 25LM)**  
**Pretreatment: Method A**  
**Substrate: glass; without primer**  
**aluminium; without primer**

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class E</b>
<b>Resistance to flow</b>	<b>≤3 mm</b>
<b>Loss of volume</b>	<b>≤10 %</b>
<b>Secant tensile modulus at -30°C</b>	<b>≤0,9 MPa</b>
<b>Tensile properties at maintained extension at -30°C</b>	<b>Pass</b>
<b>Adhesion/cohesion properties after exposure to heat water and artificial light</b>	<b>Pass</b>
<b>Elastic recovery</b>	<b>≥60 %</b>
<b>Durability</b>	<b>Pass</b>
<b>Release of dangerous substances</b>	<b>Vedi SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 27/09/2019

**www.kerakoll.com**

**KERAKOLL FRANCE** au capital de € 6.500.000  
25 Avenue de l'Industrie - 69960 Corbas, Fran  
Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



## DECLARATION OF PERFORMANCE No. 0337

1. Unique identification code of the product-type: **RESYLSANIT**
2. Intended use/es: **Sealant for non-structural use: sanitary joints .**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
5. Harmonised standard: **EN 15651-3:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
6. Declared performance/s:  
**EN15651-3 S (Class XS1)**  
**Pretreatment: Method A**  
**Substrate: glass; without primer**  
**aluminium; without primer**

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class E</b>
<b>Resistance to flow</b>	<b>≤ 3 mm</b>
<b>Loss of volume</b>	<b>≤ 20%</b>
<b>Tensile properties at maintained extension after immersion in water</b>	<b>Pass</b>
<b>Microbiological growth</b>	<b>1</b>
<b>Durability</b>	<b>Pass</b>
<b>Release of dangerous substances</b>	<b>See SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 27/09/2019

**www.kerakoll.com**

KERAKOLL FRANCE au capital de € 6.500.000,00  
25 Avenue de l'Industrie - 69960 Corbas, France  
Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



## DECLARATION OF PERFORMANCE No. 0337

1. Unique identification code of the product-type: **RESYLSANIT**
2. Intended use/es: **Sealant for movement joints in floors for interior and exterior application, for non-structural use; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:  
**System 3 and System 4 for reaction to fire**
5. Harmonised standard: **EN 15651-4:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
6. Declared performance/s:  
**EN15651-4 PW-EXT-INT-CC (Classe 12,5 E)**  
**Pretreatment: Method A**  
**Substrate: mortar M1 with primer**

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class E</b>
<b>Loss of volume</b>	<b>≤ 15%</b>
<b>Tensile properties at maintained extension</b>	<b>Pass</b>
<b>Adhesion / cohesion properties at maintained extension after water immersion</b>	<b>Pass</b>
<b>Adhesion / cohesion properties at maintained extension after salt water immersion</b>	<b>Pass</b>
<b>Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)</b>	<b>Pass</b>
<b>Tear resistance</b>	<b>Pass</b>
<b>Durability</b>	<b>Pass</b>
<b>Release of dangerous substances</b>	<b>Vedi SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (General Manager)**

At Corbas, on 27/09/2019

**www.kerakoll.com**

KERAKOLL FRANCE au capital de € 6.500.000  
25 Avenue de l'Industrie - 69960 Corbas, Fran  
Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mai  
Siret 809 032 469 00011



**KERAKOLL**  
The GreenBuilding Company



**[www.kerakoll.com](http://www.kerakoll.com)**

**KERAKOLL FRANCE** au capital de € 6.500.000,00  
25 Avenue de l'Industrie - 69960 Corbas, France  
Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: [info@kerakoll.fr](mailto:info@kerakoll.fr)  
Siret 809 032 469 00011