# kerakoll

### DECLARATION OF PERFORMANCE No. 0372

- 1. Unique identification code of the product-type: HYPERFLEX PU
- 2. Intended use/es: Sealant for external and internal, non-structural use: facade joints; included cold climates.
- 3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas France
- 4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-1:2012 Notified body/ies: GINGER CEBTP, No. 0074

Laboratoire National de metrologie et d'Essais, No. 0071

6. Declared performance/s:

EN15651-1 F-EXT-INT -CC (Class 25 LM)

#### **Pretreatment: Method A**

Substrate: aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties at maintained extension after water immersion	Pass
Secant modulus for non-structural low modulus sealants used in joints in cold climate areas (-30°C)	≤ 0,9 MPa
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	Pass
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 04/09/2020

## kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr Siret 809 032 469 00011

# kerakoll

### **DECLARATION OF PERFORMANCE No. 0372**

- 1. Unique identification code of the product-type: HYPERFLEX PU
- 2. Intended use/es: Sealant for movement joints in floors for interior and exterior application, for non-structural use; included cold climates.
- 3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas France
- 4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-4:2012

Notified body/ies: GINGER CEBTP, No. 0074

Laboratoire National de metrologie et d'Essais, No. 0071

6. Declared performance/s:

EN15651-4 PW-EXT-INT-CC (Classe 25 LM)

Pretreatment: Method A

Substrate: aluminium; without primer

Essential characteristics		Performance
Reaction to fire		Class E
Loss of volume		≤ 10%
Tensile properties at maintained extension		Pass
Adhesion / cohesion properties at maintained extension immersion	after water	Pass
Adhesion / cohesion properties at maintained extension immersion	after salt water	Pass
Secant modulus for non-structural low modulus sealants used in joints in cold climate areas (-30°C)		≤ 0,9 MPa
Tensile properties at maintained extension for non-structure used in joints in cold climates area (-30°C)	ctural sealants	Pass
Tear resistance		Pass
Durability		Pass
Release of dangerous substances		Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 04/09/2020

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: info@kerakoll.fr Siret 809 032 469 00011