



# kerakoll

## DECLARATION OF PERFORMANCE No. 0421

1. Unique identification code of the product-type: **SILICONE COLOR**
2. Intended use/es: **Sealant for external and internal, non-structural use: facade joints; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas – France**
4. Importer: **Tilemaster Adhesives Ltd – Kerakoll Group – Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK**
5. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
6. Harmonised standard: **BS EN 15651-1:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
7. Declared performance/s:  
**EN15651-1 F-EXT-INT-CC (Class 25 LM)**  
**Pretreatment: Method A**  
**Substrate: glass; without primer**  
**aluminium without primer**  
**mortar M1 with primer**

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤3 mm
Loss of volume	≤10 %
Tensile properties at maintained extension after water immersion	Pass
Secant tensile modulus at -30°C	≤0,9 MPa
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	Pass
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 18/07/2022

**kerakoll.com**

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



# kerakoll

## DECLARATION OF PERFORMANCE No. 0421

1. Unique identification code of the product-type: **SILICONE COLOR**
2. Intended use/es: **Sealant used for sealing glazing applications; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas – France**
4. Importer: **Tilemaster Adhesives Ltd – Kerakoll Group – Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK**
5. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
6. Harmonised standard: **BS EN 15651-2:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
7. Declared performance/s:  
**EN15651-2 G-CC (Class 25LM)**  
**Pretreatment: Method A**  
**Substrate: glass; without primer**  
**aluminium; without primer**

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤3 mm
Loss of volume	≤10 %
Secant tensile modulus at -30°C	≤0,9 MPa
Tensile properties at maintained extension at -30°C	Pass
Adhesion/cohesion properties after exposure to heat water and artificial light	Pass
Elastic recovery	≥60 %
Durability	Pass
Release of dangerous substances	Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 18/07/2022

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr  
Siret 809 032 469 00011



# kerakoll

## DECLARATION OF PERFORMANCE No. 0421

1. Unique identification code of the product-type: **SILICONE COLOR**
2. Intended use/es: **Sealant for non-structural use: sanitary joints .**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas – France**
4. Importer: **Tilemaster Adhesives Ltd – Kerakoll Group – Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK**
5. System/s of AVCP:  
**System 3 and System 3 for reaction to fire**
6. Harmonised standard: **BS EN 15651-3:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
7. Declared performance/s:  
**EN15651-3 S (Class XS1)**  
**Pretreatment: Method A**  
**Substrate:     glass; without primer**  
**aluminium; without primer**

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 20%
Tensile properties at maintained extension after immersion in water	Pass
Microbiological growth	1
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 18/07/2022

**kerakoll.com**

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 – Fax +33 (0) 4 72 89 06 81 – e-mail: [info@kerakoll.fr](mailto:info@kerakoll.fr)  
Siret 809 032 469 00011



# kerakoll

## DECLARATION OF PERFORMANCE No. 0421

1. Unique identification code of the product-type: **SILICONE COLOR**
2. Intended use/es: **Sealant for movement joints in floors for interior and exterior application, for non-structural use; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas – France**
4. Importer: **Tilemaster Adhesives Ltd – Kerakoll Group – Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK**
5. System/s of AVCP:  
**System 3 and System 4 for reaction to fire**
6. Harmonised standard: **BS EN 15651-4:2012**  
Notified body/ies: **SKZ – TeConA GmbH, No. 1213**
7. Declared performance/s:  
**EN15651-4 PW-EXT-INT-CC (Classe 12,5 E)**  
**Pretreatment: Method A**  
**Substrate: mortar M1 with primer**

Essential characteristics	Performance
Reaction to fire	Class E
Loss of volume	≤ 15%
Tensile properties at maintained extension	Pass
Adhesion / cohesion properties at maintained extension after water immersion	Pass
Adhesion / cohesion properties at maintained extension after salt water immersion	Pass
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	Pass
Tear resistance	Pass
Durability	Pass
Release of dangerous substances	Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (General Manager)**

At Corbas, on 18/07/2022

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr  
Siret 809 032 469 00011