

kerakoll

DECLARATION OF PERFORMANCE No. 0529

1. Unique identification code of the product-type: COLORSIL

2. Intended use/es: Sealant for external and internal, non-structural use: facade joints.

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: **EN 15651-1:2012**

Notified body/ies: GINGER CEBTP, No. 0074

Laboratoire National de metrologie et d'Essais, No. 0071

6. Declared performance/s:

EN15651-1 F-EXT-INT-CC (Class 25 LM)

Pretreatment: Method A


Substrate: aluminium without primer mortar M2 without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow Loss of volume Tensile properties at maintained extension after water immersion Secant tensile modulus at -30°C Tensile properties at maintained extension for non-structural sealants used in joints in cold climates areas (-30°C) Durability	≤ 3 mm ≤ 10% Pass ≤ 0.9MPa Pass Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 24/05/2022



kerakoll.com



kerakoll

DECLARATION OF PERFORMANCE No. 0529

1. Unique identification code of the product-type: COLORSIL

2. Intended use/es: Sealant for non-structural use: glazing application

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-2:2012

Notified body/ies: GINGER CEBTP, No. 0074

6. Declared performance/s:

EN15651-2 G-CC (Class 25 LM)

Pretreatment: Method A

Substrate: glass without primer

aluminium without primer

Essential characteristics		Performance
Reaction to fire		Class E
Resistance to flow Loss of volume Secant tensile modulus at -30°C Tensile properties at maintained extension at -30°C Adhesion / cohesion properties after exposure to heat, artificial light Elastic recovery Durability	water and	≤ 3 mm ≤ 10% ≤ 0,9 MPa Pass Pass ≥ 60% Pass
Release of dangerous substances		See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 24/05/2022

kerakoll.com



kerakoll

DECLARATION OF PERFORMANCE No. 0529

1. Unique identification code of the product-type: COLORSIL

2. Intended use/es: Sealant for non-structural use: sanitary joints.

3. Manufacturer: Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France

4. System/s of AVCP:

System 3 and System 3 for reaction to fire

5. Harmonised standard: EN 15651-3:2012

Notified body/ies: GINGER CEBTP, No. 0074

Laboratoire National de metrologie et d'Essais, No. 0071

6. Declared performance/s:

EN15651-3 S (Class XS3)

Pretreatment: Method A

Substrate: aluminium; without primer mortar M2; without primer

Essential characteristics		Performance
Reaction to fire		Class E
Resistance to flow		≤ 3 mm
Loss of volume		≤ 20%
Tensile properties at maintained extension after water in	nmersion	Pass
Microbiological growth		4
Durability		Pass
Release of dangerous substances		See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Etienne Guichard (legal representative)

At Corbas, on 24/05/2022



kerakoll.com