



kerakoll

DECLARATION OF PERFORMANCE No. 0611

1. Unique identification code of the product-type: **SILMAT COLOR**
2. Intended use/es: **Sealant for external and internal, non-structural use: facade joints; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:
System 3 and System 3 for reaction to fire
5. Harmonised standard: **EN 15651-1:2012**
Notified body/ies: **Ginger Cebtp 0074**
Istituto Giordano n° 0407
6. Declared performance/s:
EN15651-1 F-EXT-INT-CC (Class 25 LM)
Pretreatment: Method B
Substrate: anodized aluminum; without primer
mortar M2; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤3 mm
Loss of volume	≤10 %
Tensile properties at maintained extension after water immersion	Pass
Secant tensile modulus at -30°C	≤0,9 MPa
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	Pass
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 18/09/2023

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr
Siret 809 032 469 00011



kerakoll

DECLARATION OF PERFORMANCE No. 0611

1. Unique identification code of the product-type: **SILMAT COLOR**
2. Intended use/es: **Sealant for non-structural use: sanitary joints .**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:
System 3 and System 3 for reaction to fire
5. Harmonised standard: **EN 15651-3:2012**
Notified body/ies: **Ginger Cebtp 0074**
Istituto Giordano n° 0407
6. Declared performance/s:
EN15651-3 S (Class XS1)
Pretreatment: Method B
Substrate: glass; without primer
anodized aluminium; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties at maintained extension after immersion in water	Pass
Microbiological growth	0
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (legal representative)**

At Corbas, on 18/09/2023

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.000,00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr
Siret 809 032 469 00011



kerakoll

DECLARATION OF PERFORMANCE No. 0611

1. Unique identification code of the product-type: **SILMAT COLOR**
2. Intended use/es: **Sealant for movement joints in floors for interior and exterior application, for non-structural use; included cold climates.**
3. Manufacturer: **Kerakoll France 25, avenue de l'Industrie 69960 Corbas - France**
4. System/s of AVCP:
System 3 and System 3 for reaction to fire
5. Harmonised standard: **EN 15651-4:2012**
Notified body/ies: **Ginger Cebtp 0074**
Istituto Giordano n° 0407
6. Declared performance/s:
EN15651-4 PW-EXT-INT-CC (Classe 25LM)
Pretreatment: Method B
Substrate: mortar M2; without primer

Essential characteristics	Performance
Reaction to fire	Class E
Loss of volume	≤ 10%
Tensile properties at maintained extension	Pass
Adhesion / cohesion properties at maintained extension after water immersion	Pass
Adhesion / cohesion properties at maintained extension after salt water immersion	Pass
Tensile properties at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C)	Pass
Tear resistance	Pass
Secant tensile modulus at -30°C	≤ 0,9 MPa
Durability	Pass
Release of dangerous substances	Vedi SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Etienne Guichard (General Manager)**

At Corbas, on 18/09/2023

kerakoll.com

KERAKOLL FRANCE - au capital de € 6.500.00

25 Avenue de l'Industrie - 69960 Corbas, France - Tél +33 (0) 4 72 89 06 80 - Fax +33 (0) 4 72 89 06 81 - e-mail: info@kerakoll.fr
Siret 809 032 469 00011