kerakoll

DECLARATION OF PERFORMANCE No 0015

- 1. Unique identification code of the product-type: BIOCALCE MURATURA FINO
- 2. Intended use/es: General purpose masonry mortar (G) for external and internal use in elements subject to structural requirements
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 2+

System 4 for reaction to fire

5. Harmonised standard: EN 998-2:2010

Notified body/ies: LRQA Iberia No.0094

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1
Compressive strength	M10
Initial shear strength	0,2 N/mm ²
Contents of chloride	≤ 0,05%
Water absorption	0,7 Kg/(m² min ^{0,5})
Water vapour permeability	μ 15/35 (v.t.)
Thermal conductivity	0,83 W/mK (v.t)
Durability	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

At Sassuolo, on 05/05/2025

Profrede ..

Kerakoll Spa via dell'Artigianato 9 41049 Sassuolo (MO) Italia Società con unico socio Fin Firel Spa. Soggetta a direzione e coordinamento di Fin Firel Spa. +39 0536816511 +39 0536816581 info@kerakoll.com www.kerakoll.com Rea MO n. 231812 R.I./C.F./P.I. 01174510360 Cap. soc. € 2.000.000,00 i.v.