



## DECLARATION OF PERFORMANCE No 0024

- 1. Unique identification code of the product-type: CEMENTOCRUDO 3 NEW
- 2. Intended use/es: Surface protection products according to principles 1 (PI) and 5 (PR) Impregnation
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP: System 2+ and System 4 for reaction to fire
- 5. Harmonised standard: EN 1504-2:2004

Notified body/ies: S.G.S. Italia No.1381

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class F
Abrasion resistance	≥30%
Capillary absorption and permeability water vapour	w ≤ 0,1 kg <sup>*</sup> m <sup>-2 *</sup> h <sup>-0,5</sup>
Impact resistance	Class I
Adhesion strength by pull off test	≥ 1,5 N/mm²
Depth of Penetration	> 5 mm
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

At Sassuolo, on 15/06/2018

Mofrede

## www.kerakoll.com

KERAKOLL Spa - Single Member Company - Fin Firel Spa - via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia Tel +39 0536 816 511 - Fax +39 0536 816 581