kerakoll

DECLARATION OF PERFORMANCE No 0041

- 1. Unique identification code of the product-type: GEOLITE GEL
- 2. Intended use/es: Structural bonding product for bonded plate reinforcement
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 2+

System 3 for reaction to fire

5. Harmonised standard: EN 1504-4:2005 Notified body/ies: SGS Italia Nr. 1381

Istituto Giordano Nr. 0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class C-s2, d0
Bond/adhesion strength :	
- Pull off strength	≥ 14 N/mm²
- Slant shear strength at 50°	≥ 50 N/mm²
- Slant shear strength at 60°	≥ 60 N/mm²
- Slant shear strength at 70°	≥ 70 N/mm²
Shear strength	≥ 12 N/mm²
Shrinkage/expansion	≤ 0,1%
Workability	75 min at 20°C
Modulus of elasticity	≥ 2000 N/mm²
Coefficient of thermal expansion	≤ 100 x 10 ⁻⁶ per K
Glass transition temperature	≥ 40°C
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

At Sassuolo, on 12/08/2020

Mofrede ..

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.

kerakoll

DECLARATION OF PERFORMANCE No 0041

- 1. Unique identification code of the product-type: GEOLITE GEL
- 2. Intended use/es: Anchoring product of reinforcing steel bar
- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:
 - System 2+

System 3 for reaction to fire

5. Harmonised standard: EN 1504-6:2007

Notified body/ies: SGS Italia Nr. 1381

Istituto Giordano Nr. 0407

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class C-s2, d0
Pull-out	≤ 0,6 mm
Creep under tensile load	≤ 0,6 mm
Glass transition temperature	≥ 45°C
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

At Sassuolo, on 12/08/2020

Profrede ...

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.