



DECLARATION OF PERFORMANCE No 0052

- 1. Unique identification code of the product-type: H40 ECO RAPID
- 2. Intended use/es:

Improved fast setting cementitious adhesive for ceramic tiling, all internal and external tiling

- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. System/s of AVCP:

System 3
System 4 for reaction to fire

5. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Instituto Tecnológico de la Construcción AIDICO No. 1170

6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A1/A1 _{fl}
Bond strength as:	
early tensile adhesion strength	≥ 0,5 N/mm²
initial tensile adhesion strength	≥ 1,0 N/mm²
Durability for:	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

Sassuolo 03/11/2020

Mylede