



DECLARATION OF PERFORMANCE No. 0059

1. Unique identification code of the product-type: **KERABUILD EPOPRIMER**
2. Intended use/es: **Structural bonding product for bonded mortar or concrete**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
5. Harmonised standard: **EN 1504-4:2004**
Notified body/ies: **SGS Italia Nr. 1381**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class F
Bond/adhesion strength	Pass
Compressive strength	≥ 30 N/mm²
Shear strength	≥ 6 N/mm²
Shrinkage/expansion	≤ 0,1%
Workability	40 min at 20°C
Sensitivity to water	Pass
Modulus of elasticity	≥ 2000 N/mm²
Coefficient of thermal expansion	≤ 100 x 10⁻⁶ per K
Glass transition temperature	≥ 40°C
Durability	Pass
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 15/05/2020