



DECLARATION OF PERFORMANCE No 0063

1. Unique identification code of the product-type: **KERABUILD ECO OSMOCEM**
2. Intended use/es:
Surface protection products according to principles 1 (PI), 2 (MC), 6 (RC) and 8 (IR) - Coating
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 2+
System 4 for reaction to fire
5. Harmonised standard: **EN 1504-2:2004**
Notified body/ies: **S.G.S. Italia No.1381**
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A₁
Permeability to CO₂	S_D > 50 m
Permeability to water vapour	Classe I, S_D < 5 m
Resistance to severe chemical attack	CR1, CR2, CR3, CR4, CR5, CR6, CR8, CR11, CR15 (Class II), CR12 (Class I)
Capillary absorption and permeability to water	w ≤ 0,1 Kg/m² h^{0,5}
Adhesion strength by pull-off test	≥ 0,8 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**
At Sassuolo, on 17/11/2020