

## kerakoll

## **DECLARATION OF PERFORMANCE No 0097**

- 1. Unique identification code of the product-type: AQUASTOP NANOFLEX CM 01P
- 2. Intended use/es:

Cementitious liquid-applied water impermeable product for external installation on wall, floor and swimming pools, beneath ceramic tilling. (bonded with C2 adhesive in accordance with EN 12004)

- 3. Manufacturer: Kerakoll S.p.A Via dell'Artigianato, 9 41049 Sassuolo (MO) Italia
- 4. Importer: Kerakoll UK Ltd- Tomlinson Road, Leyland, Lancanshire, PR25 2DY, UK.
- 5. System/s of AVCP:

System 3 for waterproofing
System 4 for all the charateristics other than waterproofing

6. Harmonised standard: BS EN 14891:2012+AC:2012

Notified body/ies: Modena Centro Prove No.1599

7. Declared performance/s:

Essential characteristics	Performance
Initial tensile adhesion strength	≥ 0,5 N/mm <sup>2</sup>
Tensile adhesion strength after water contact	≥ 0,5 N/mm <sup>2</sup>
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm²
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm²
Waterproofing	No penetration
Crack bridging ability	≥ 0,75 mm
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm <sup>2</sup>
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Romano Sghedoni (legal representative)

Sassuolo 01/06/2024

Medei