



kerakoll

DECLARATION OF PERFORMANCE No 0358

1. Unique identification code of the product-type: **H40 EXTREME**
2. Intended use/es: **Improved reaction resin adhesive for all internal and external tiling**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. Importer: **Tilemaster Adhesives Ltd - Kerakoll Group - Tomlinson Road, Leyland, Lancashire, PR25 2DY, UK.**
5. System/s of AVCP:
System 3
6. Harmonised standard: **BS EN 12004:2007 + A1:2012**
Notified body/ies: **Lucideon No. 1289**
WARRINGTON FIRE No. 0833
7. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class B2-s1, d0
Bond strength as: initial shear adhesion strength	≥ 2,0 N/mm²
Durability for: shear adhesion strength after thermal shock shear adhesion strength after water immersion	≥ 2,0 N/mm² ≥ 2,0 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Filippo Iacconi (General Manager)**

At Leyland, on 01/12/2021

www.kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.