



kerakoll

DECLARATION OF PERFORMANCE No 0392

1. Unique identification code of the product-type: **KLIMA FLEX**
2. Intended use/es: **General purpose mortar (GP) for use in external/internal masonry**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 4
System 4 for reaction to fire
5. Harmonised standard: **EN 998-1:2016**
Notified body/ies: -
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1,d0
Adhesion	$\geq 1,1$ N/mm² FP:B
Water absorption	W_c 2
Water vapour diffusion coeff.	μ 15
Thermal conductivity	0,44 W/mK (tab. Value)
Durability (agaist freeze/thaw)	NPD
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

At Sassuolo, on 26/03/2018

kerakoll.com

KERAKOLL Spa - Società con unico socio Fin Firel Spa - Soggetta a direzione e coordinamento di Fin-Firel Spa
via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia - Tel +39 0536 816 511 - Fax +39 0536 816 581 - e-mail: info@kerakoll.com
Rea MO n. 231812 - Reg. Imp. / Cod. Fisc. / P. Iva IT 01174510360 - Cap. Soc. € 2.000.000,00 i.v.