



**DECLARATION OF PERFORMANCE No 0473**

1. Unique identification code of the product-type: **KLIMA LIGHT**
2. Intended use/es: **General purpose mortar (GP) for use in external/internal masonry**
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:  
**System 4**  
**System 4 for reaction to fire**
5. Harmonised standard: **EN 998-1:2016**  
Notified body/ies: -
6. Declared performance/s:

Essential characteristics	Performance
<b>Reaction to fire</b>	<b>Class A1</b>
<b>Adhesion</b> <b>Water absorption</b> <b>Water vapour diffusion coeff.</b> <b>Thermal conductivity</b> <b>Durability (agaist freeze/thaw)</b>	<b>≥ 1,0 N/mm<sup>2</sup> FP:B</b> <b>W<sub>c</sub> 2</b> <b>μ 11</b> <b>0,27 W/mK</b> <b>NPD</b>
<b>Release of dangerous substances</b>	<b>See SDS</b>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**  
At Sassuolo, on 09/03/2020