



DECLARATION OF PERFORMANCE No 0523

1. Unique identification code of the product-type: **AQUASTOP EXTREME**
2. Intended use/es:
Reaction resin liquid-applied water impermeable product for external installations on walls, floors and swimming pools, beneath ceramic tiling (bonded with R2 adhesive in accordance with EN 12004)
3. Manufacturer: **Kerakoll S.p.A Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italia**
4. System/s of AVCP:
System 3 for waterproofing
System 4 for all the characteristics other than waterproofing
5. Harmonised standard: **EN 14891:2012+AC:2012**
Notified body/ies: **Modena Centro Prove No.1599**
6. Declared performance/s:

Essential characteristics	Performance
Initial tensile adhesion strength	≥ 0,5 N/mm²
Tensile adhesion strength after water contact	≥ 0,5 N/mm²
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm²
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm²
Waterproofing	No penetration
Crack bridging ability (+ 23 °C)	≥ 0,75 mm
Crack bridging ability (- 5 °C)	≥ 0,75 mm
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm²
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Romano Sghedoni (legal representative)**

Sassuolo , 02/04/2021