

## **DECLARATION OF PERFORMANCE No 0238**

1. Unique identification code of the product-type: H40 BEZ LIMITÓW

Intended use/es:

Improved cementitious adhesive for all internal and external tiling.

2. Manufacturer: Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów

3. System/s of AVCP:

System 3

System 3 for reaction to fire

4. Harmonised standard: EN 12004:2007 + A1:2012

Notified body/ies: Modena Centro Prove No. 1599

Istituto Giordano No. 0407

**5.** Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1, d0
Bond strength expressed as:- initial tensile adhesion strength	≥ 1,0 N/mm²
Durability of bond strength against climate/heat ageing action expressed as: tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
Durability of bond strength against water/humidity action expressed as: tensile adhesion strength after water immersion	≥ 1,0 N/mm²
Durability of bond strength against freeze-thaw cycles expressed as: tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm²
Release of dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Jacek Szczycinski (legal representative)

Jacob Snych