

DECLARATION OF PERFORMANCE No 0565

1. Unique identification code of the product-type:
Aquaform Optima profil, Aquaform Optima NZ90, Aquaform Optima NW90, Aquaform Optima NZ135, Aquaform Optima NW135, Aquaform Optima L
2. Intended use/es:
Eaves profiles for terraces and balconies
3. Manufacturer:
Kerakoll Polska sp. z o.o., ul. Katowicka 128, 95-030 Rzgów
4. System/s of AVCP:
System 3
5. European Assessment Document:
EAD 220008-00-0402
European Technical Assessment:
ETA-22/0190 z 14/03/2022
Technical Assessment Body:
Instytut Techniki Budowlanej, ul. Filtrowa 1, 00-611 Warszawa, No 1488
6. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	Class A2-s1,d0
Coating thickness	≥ 60 μm
Adhesion	0
Indentation	≥ 80
Acetic acid salt spray resistance, testing time: 1000 hours	No blistering in excess of 2 (S2) according to ISO 4628-2. An infiltration of maximum 16 mm ² is allowed over a scratch length of 100 mm but the length of any single infiltration shall not exceed 4 mm
Resistance to humid atmospheres containing sulphur dioxide (0,2 l SO ₂ - 24 cycles)	No infiltration exceeding 1 mm on both sides of the scratch, and no change in colour or blisters in excess of 2 (S2) according to ISO 4628-2
note: the coating has a QUALICOAT mark corresponding to the abovementioned performance	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer: **Jacek Szczycinski (legal representative)**



At Rzgów, on 22/02/2023