

Finish

Protective water-based impregnating finish for Patina® and Patina® Living resin coverings.

Patina® and Patina® Living are water based resin coverings with a delabrè plaster texture and natural shaded finish.

Patina® is a specific cycle for bathroom and kitchen coverings; Patina® Living is the decorative finish suitable for the walls of all other types of environments.

Italian design for living comfort.



Rating 4

- × VOC Low Emission
- ✓ Water based
- ✓ Solvent ≤ 80 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

1. Ready-to-use
2. Easy to apply with a brush
3. Does not alter the treated surfaces

Areas of application

→ Intended use:

- Water-based impregnating protective product
- Water-based impregnating protective product for Patina coloured texturizing finishing coat

→ Internal use in domestic, commercial and industrial environments.

Do not use

On substrates which are dirty, non-cohesive, powdery.

In the presence of rising damp, without suitable dehumidifying systems.

Instructions for use

→ Preparation of substrates

- Patina Living: once the Patina coloured texturizing finishing coat has completely dried, apply the 1st coat of Finish. After 4 - 6 hours, sand the surface with 80 - 120 grain sandpaper in order to remove any small imperfections and to make the surface smooth and pleasing to the touch. Remove any dust with a dry flat brush or a cotton cloth before applying the 2nd coat of Finish.
- Patina: once the Patina coloured texturizing finishing coat has completely dried, apply one coat of Finish. After 4 - 6 hours, sand the surface with 80 - 120 grain sandpaper in order to remove any small imperfections and to make the surface smooth and pleasing to the touch. Remove any dust with a dry flat brush or a cotton cloth before applying 3 coats of Microresina Xtreme Invisible.

→ Preparation

Ready-to-use. Remix the product inside the container to ensure the mixture is of an even consistency.

→ Application

Apply Finish using a flat brush and crossing the brush strokes, spreading it from the bottom upward. Avoid percolation and apply the product continuously.

→ Cleaning

The tools can be cleaned with water before the product hardens.

Special notes

- Apply Finish at temperatures from +10 °C to +30 °C and relative ambient humidity lower than 80%.
- Particular care must be taken when carrying out decorations over full backgrounds. Avoid interruptions between scaffolding levels or on large continuous surfaces.
- Any splashes of product must be removed immediately with clean water.

- The photographic images in the catalogue and on the website, as well as the colours shown in the samples are to be considered purely indicative.
- Use material from a single production batch for each project.
- Materials from different batches may have slight colour and sheen variations.

Certificates and marks



Technical Data compliant with Kerakoll Quality Standard

Appearance	milky liquid
Volumetric mass	≈ 0.99 kg/l
Shelf life	≈ 12 months from production in the original sealed packaging
Pack	buckets 1.5 l
Temperature range for application	from +10 °C to +30 °C
Dust free	≈ 30 min.
Humidity of the substrate	≤ 6%
Waiting time between 1 st and 2 nd coat	4 - 6 hrs
Average coverage per single coat	0.07 – 0.08 l/m ²

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate

Warning

- | | |
|--|---|
| → Product for professional use | → dispose of as indicated in applicable legislation |
| → abide by any standards and national regulations | → protect any surfaces and objects in the application area from accidental contact with the product |
| → use at temperatures between +5 °C and +30 °C | → if necessary, ask for the safety data sheet |
| → apply on dry substrates | → for any other issues, contact the Kerakoll Worldwide Global Service 01772 456 831 - info@kerakoll.co.uk |
| → do not add binders or additives | |
| → protect from direct sunlight and currents of air for the first 6 hours | |
| → do not apply on dirty or loose surfaces | |

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in January 2021 (ref. GBR Data Report - 02.21); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.