

Fugalite Cleaning Kit

kerakoll

Fugalite products



Fugalite Color

Waterproof decorative resin for the grouting and bonding of ceramic tiles, mosaics and natural stones. Easy to clean, stain-proof.



Fugalite Invisible

Waterproof, photochromatic, decorative resin for the grouting and bonding of glass mosaic and low-thickness ceramic tiles. Guarantees aesthetic continuity.

Detergents and cleaners



Fuga-Wash

Detergent to be used as an additive in water used to clean Fugalite.

- Facilitates cleaning of covering materials
- Keeps the sponge cleaner



Fuga-Soap

Detergent for removing streaks of Fugalite.

- Ideal for cleaning after fixing
- Suitable for all surfaces



Fuga-Shock

Ready-to-use cleaner for removing residues and streaks of epoxy resins.

- Highly effective
- Floors and walls

Sponges and accessories



Rubber spreader

Rubber spreader for Fugalite application.
Guarantees complete filling of the gap.

→ APPLICATION



Cellulose sponge

Natural cellulose sponge with support plate for handle.
Powerful cleaning.
Stays clean for longer.

→ CLEANING



Abrasive felt

White abrasive felt pad with support plate for handle and felt pad.
Effective mechanical action.

→ CLEANING AND ABRASION



Foam rubber sponge

Fine pore foam rubber sponge with support plate for handle.
ideal for extra fine finishing.

→ SMOOTHING

Preparation



1.



First cleaning with a rubber spreader

once the joints have been filled, remove any excess grout that is left on the tiles immediately with the rubber spreader (working diagonally).

2.



The addition of Fuga-Wash to the cleaning water

Recommended dosage: 1 measuring cap for every 5 litres of water. Use washboy **A** to carry out the first cleaning pass with a cellulose sponge or abrasive felt pad, removing any excess grout from the flooring.

Use washboy **B** to carry out the second and final cleaning pass, finishing and smoothing the grout in the joint.

Change the washing water frequently so that it is always clean. Replace the sponge or felt pad if they become saturated with product.

First pass



3.



Cleaning with a cellulose sponge

Clean when the grout is still fresh, using a cellulose sponge dampened with water from washboy **A**. Use circular movements to soften the film of grout on the tiles and finish the joints. Collect the emulsion formed on the tiles using the sponge.

4.



Cleaning with an abrasive felt pad for structured surfaces

For more structured surfaces, clean when the grout is still fresh, using a felt pad dampened with the water from washboy **A**.

Use circular movements to soften the film of grout on the tiles and finish the joints. Collect the emulsion formed on the tiles using the sponge.

Second pass



5.



Finishing with a cellulose sponge

Finish cleaning with a cellulose sponge dampened with water from washboy **B**, working diagonally to the tiles so as not to dig into the joints. Do not walk on the damp floors for at least 12 - 24 hours, to avoid leaving dirt.

6.



Finishing with a foam rubber sponge for a smoother joint

For a smooth finish, complete cleaning with a foam rubber-sponge dampened with water from washboy **B**, working diagonally to the tiles so as not to dig into the joints.

The following day

- Once the grout has dried, any traces of dirt and streaks can be removed using Fuga-Soap; to be diluted in accordance with the amount of grout to be removed, and the curing time for Fugalite Color.
Recommended dosage:
2 - 3 parts water to
1 part Fuga-Soap on the day after; undiluted after 3 days.
- Distribute the product over the surface to be treated, using the abrasive felt pad and leaving a thin, even film of liquid.
Leave the Fuga-Soap to work between 10 – 30 minutes.
- Collect the detergent solution with the sponge, rubber scraper or liquid vacuum system for large surfaces.
Rinse thoroughly with clean water.
- Dry immediately with a dry cloth or liquid vacuum system, without allowing the residual water to evaporate.



Special cleaning

When the grout has hardened (after at least 7 days), any residue and streaks can be removed using Fuga-Shock. Distribute the product undiluted over the surface to be treated, using the abrasive felt pad. Allow the Fuga-Shock to act for approximately 3 - 5 minutes, then carry out the indicated rinsing and drying operations the day after application.

kerakoll



kerakoll.com