

# Keradecor Wood

**High-protection impregnating gel, high UV rays resistance and to atmospheric agents.**

Keradecor Wood is a vegetable-oil, special gel type formulation which means it will not drip in vertical applications. Provides protection against fungal and bacterial attack. Internal, external.



## GREENBUILDING RATING®



Product with none of the requisites of the GreenBuilding Rating®, must be used with care. Kerakoll® undertakes to improve the ratings of Ecozero materials and products

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

## PRODUCT STRENGTHS

- The special gel formulation means it will not drip when applied to ceilings
- Excellent protection against the water-drop effect of water
- High resistance to UV rays
- Contains protective, fungicide additive
- Easy to apply with a brush or roller



## AREAS OF USE

### Use

Impregnating agent for:

- external wood products
- visible wooden beams
- wood doors and windows

For internal and external use.

### Do not use

On metal surfaces and mineral plasters/renders.

## INSTRUCTIONS FOR USE

### Preparation of substrates

**Unpainted wooden surfaces:** clean the surface thoroughly and sand with fine grain sandpaper if necessary to eliminate imperfections. Apply Keradecor Wood to the dry surface.

**Previously painted wooden surfaces:** if there is old paint or varnish, remove it or sand it until the original wooden surface can be seen, in order to highlight the natural veining. Clean and then apply Keradecor Wood to the dry surface.

### Preparation

Keradecor Wood is ready-to-use. Always remix the product before application.

\* ÉMISSION DANS L'AIR INTÉRIEUR Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

## INSTRUCTIONS FOR USE

### Application

Keradecor Wood can be applied with a brush or roller.

The product can be applied in one or more coats, according to the intensity required. Wait 12 – 24 hours between successive coats. Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and relative ambient humidity lower than 80%.

### Cleaning

Residual traces of Keradecor Wood can be removed from tools using Keradecor Eco Solmix before the product hardens.

## SPECIAL NOTES

The colour chart is provided as a general indication only. We therefore recommend testing the product onsite to check the exact colour and coverage that will be obtained.

Do not apply the product or suspend its application in the presence of wind, smoke or dust, protect surfaces from rain or night-time condensation until completely dry.

## ABSTRACT

*Protection and decoration of internal and external wooden surfaces, involving application using a brush, roller or spray of a vegetable oil-based impregnating gel with a high resistance to atmospheric agents, UV light and the attack of fungi and bacteria, such as Keradecor Wood by Kerakoll Spa.*

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	neutral or coloured liquid
Volumetric mass	≈ 0,85 kg/ℓ
Chemical nature	urethane-based alkyd resins
Pack	0.75 – 2.5 ℓ tins
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Relative humidity	≤ 70%
Dust free	2 hrs
Waiting time for next application	12 – 24 hrs
Drying	36 – 48 hrs
Coverage	≈ 80 – 100 ml/m <sup>2</sup> per coats

*Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.*

## WARNING

### - Product for professional use

- abide by any standards and national regulations
- use at temperatures between +5 °C and +30 °C
- flammable product
- do not add binders or additives
- if necessary, ask for the safety data sheet
- as it does not have sufficient resistance to abrasion, the product is not suitable to decorate and protect wooden floors that are subject to foot traffic
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2012. This information was last updated in November 2017 (ref. GBR Data Report - 11.17); please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL Spa shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)