

Keradecor Eco Solmix

Eco-friendly, slow evaporation thinner, ideal for use in GreenBuilding. Safeguards the environment.

Keradecor Eco Solmix is a turpentine-based product suitable for thinning alkyd, synthetic oil, impregnating glazes and solvent-based acrylic paints. Internal, external.



GREENBUILDING RATING®

Low Emission
IAQ
Indoor Air Quality

Water Based

SLV
REDUCED
Solvent ≤ 80 g/kg

Low Ecological Impact

Health Care

No environmental hazard rating

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

PRODUCT STRENGTHS

- High coverage
- Easy to apply with a brush, roller or spray
- Suitable for diluting:
 - Keradecor Smak Paint
 - Keradecor Eco Sintolite
 - Keradecor Oldstyle

AREAS OF USE

Use
Thinner for:

- Keradecor Oldstyle
- Keradecor Eco Sintolite
- Keradecor Smak Paint

Do not use
It must not be used to dilute quick-drying products or products based on chlorinated rubber resins.

INSTRUCTIONS FOR USE

Preparation
Dilute as indicated on the reference products.
Keradecor Eco Solmix is ready-to-use.

Cleaning
Keradecor Eco Solmix can be used to clean tools.

SPECIAL NOTES

Ensure suitable ventilation when using indoors.
Do not smoke or do not eat during use.

ABSTRACT

Thinning of alkyd, synthetic oil and solvent-based acrylic paints with a suitable, eco-friendly thinner such as Keradecor Eco Solmix by Kerakoll Spa, GreenBuilding Rating® 1.

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	transparent liquid
Volumetric mass	≈ 0.81 kg/ℓ
Chemical nature	mineral spirit
Pack	1 ℓ tins
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Distillation interval:	
- starting point	+140 °C
- end point	+200 °C

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- use at temperatures between +5 °C and +30 °C
- do not mix with acids or alkalis
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in November 2020 (ref. GBR Data Report - 1220); please note that additions and/or amendments may be made over time by KERAKOLL SpA, for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com