

# Keradecor Prontofox

Stabilizing primer based on pure powerful high-binding acrylic resins, ideal for use in GreenBuilding. Water-based, with low solvent content, safeguards the health of operators.

Keradecor Prontofox is suitable for cortical consolidation, guaranteeing the uniform absorption and colour of the next decorative cycle. For internal use.



**GREENBUILDING RATING®**

Water-based formulation    Solvent-free    Non-toxic and non-hazardous

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

**PRODUCT STRENGTHS**

- Ready-to-use
- High consolidating power
- Excellent substrate uniforming power
- Easy to apply with a brush, roller or spray

**AREAS OF USE**

**Use**  
Professional, water-based, consolidant for:

- new plaster that has been cured for 4 - 6 weeks
- old plasters that are still well anchored to the masonry substrate
- compact surface concrete structures
- gypsum-based plasters
- plasterboard
- surfaces with partially deteriorated synthetic decorative finishes

Interior walls.

**Do not use**  
As a screed consolidant for laying ceramic or wood, in the presence of moisture rising. On external walls.

**INSTRUCTIONS FOR USE**

**Preparation of substrates**  
Porous substrates with a limited level of cohesion must in any case be compact and absorbent, free from dust, oil or the presence of efflorescence, with no loose debris or flaky parts.  
On surfaces coated with synthetic finishes, paint or plastic coatings, remove all partially deteriorated sections that are fragmenting or separating from the substrate. The substrate must be stable, non-deformable and with no fracturing cracks.  
In the presence of mould, first treat with Kerakover Activ biocide. The substrate must be dry at the time of application. For the treatment of substrates other than those mentioned and for additional information on the types of intervention to be carried out, we recommend to consult Kerakoll's Guide to decorating and preparing substrates.

**Preparation**  
Keradecor Prontofox is ready-to-use.  
Always remix the product before application.

**Application**  
When applying the product preferably use a short bristle, synthetic fibre roller or a brush. Apply one or more coats avoiding drips, depending on the porosity and nature of the substrate to be consolidated or evened out.  
Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and a relative ambient humidity lower than 80%.

\* ÉMISSION DANS L'AIR INTÉRIEUR Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

## INSTRUCTIONS FOR USE

### Cleaning

Keradecor Prontofix can be cleaned from tools by washing them using water before the product hardens.

## SPECIAL NOTES

The use of Keradecor Prontofix on absorbent walls improves the adhesion of subsequent application cycles. In the case of very compact surfaces that are not very porous, avoid forming a shiny surface film. Wait 6 hours before the subsequent paint cycle, and in any event until the product has fully dried.

## ABSTRACT

*Fixing and evening up absorption of internal surfaces, by application using a brush, roller or spray of a water-based pure acrylic resin primer with a low solvent content, such as Keradecor Prontofix by Kerakoll Spa, GreenBuilding Rating® 3.*

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	milky white
Volumetric mass	≈ 1 kg/ℓ
Chemical nature	acrylic
Pack	1 – 5 – 10 ℓ cans
Shelf life	≈ 24 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Viscosity	25 s – Iso 3 flow cup
Temperature range for application	from +5 °C to +30 °C
Humidity of the substrate	≤ 6%
Waiting time between subsequent coats	≥ 6 hrs
Average coverage per single coat	≈ 0.1 – 0.15 ℓ/m <sup>2</sup>

*Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.*

## WARNING

### - Product for professional use

- abide by any standards and national regulations
- check that the substrate is perfectly clean, and absorbent
- the product is ready-to-use
- apply one or more coats, depending on substrate
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in November 2020 (ref. GBR Data Report - 1220); please note that additions and/or amendments may be made over time by KERAKOLL SpA, for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)