

Kerakover Activ



Ready-to-use, water-based surface restoration product, ideal for use in GreenBuilding. With low solvent content, safeguards the health of both operators and the environment.

Kerakover Activ is based on active anti-biodeteriorating agents and is suitable for the restoration of surfaces affected by deposits and colonies of mould, algae, fungi and lichen. For internal and external use.



GREENBUILDING RATING®

rating4

<p>Low Emission Indoor Air Quality</p>	<p>Water Based</p>	<p>SLV Solvent ≤ 15 g/kg</p>	<p>Low Ecological Impact</p>	<p>Health Care</p>
<p>Water-based formulation</p>	<p>Reduced solvent content 11 g/kg</p>	<p>No environmental hazard rating</p>	<p>Non-toxic and non-hazardous</p>	

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

PRODUCT STRENGTHS

- Effective against mould, algae, fungi and lichen
- Odourless
- Easy to apply
- Internal, external

AREAS OF USE

Use

- natural stone, artificial stone and cotto-covered wall surfaces, both for internal and external use
- fine stone or unusual surfaces, such as artistic moulded ones
- surfaces already covered with synthetic finishes or plastic coatings
- gypsum surfaces

For internal and external use.

Do not use

In the presence of rising damp.

INSTRUCTIONS FOR USE

Preparation of substrates

Surfaces to be treated must be solid and stable to prevent fractures from leaving some areas untreated. Protect all surfaces that could be damaged.

For the treatment of substrates other than those mentioned and for additional information on the types of intervention to be carried out, we recommend to consult Kerakoll's Guide to decorating and preparing substrates.

Preparation

Kerakover Activ is ready-to-use and does not require dilution with either solvents or water.

Application

First apply a liberal coat of the product with a brush or low pressure spray gun to the surface to be restored and leave it to set for 24 hours.

External use: clean the affected surfaces with water, preferably using a high-pressure washer, in order to remove all traces of deposits.

Internal use: rinse the affected surfaces with water and clean using brushes and scrapers to completely remove all traces of deposits. Rinse the affected surfaces afterwards with a high-pressure water jet, preferably using a high-pressure washer; assist the detergent action of the water using brushes and scrapers to remove all traces of any remaining deposits.

Repeat the application of Kerakover Activ as necessary for tougher concentrations or remaining streaks or deposits, finishing off by washing as before.

When repairing fine moulded, ornate and internal surfaces, apply the product with a brush or low pressure spray gun then rinse using water, cleaning at the same time with broomcorn brushes or scrapers until all traces of deposits have been removed.

Conditions required for decorating are ambient and substrate temperatures between +5 °C and +30 °C and a relative ambient humidity lower than 80%.

* ÉMISSION DANS L'AIR INTÉRIEUR Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

INSTRUCTIONS FOR USE

Do not apply when the substrate is directly exposed to sunlight or in heavy wind.
After application, external surfaces must be protected from rain for 24 hours.

Cleaning

Residual traces of Kerakover Activ can be removed from tools using water immediately after use.

SPECIAL NOTES

This product can cause irritation; in case of contact with the skin, rinse immediately with soap and water.

ABSTRACT

Restoration product for internal and external surfaces affected by deposits and colonies of mould, algae, fungi and lichen, involving application by brush, roller or low pressure spray of ready-to-use, water-based solutions of active anti-biodeteriorating agents with a low solvent content, such as Kerakover Activ by Kerakoll Spa, GreenBuilding Rating® 4.

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	straw-coloured liquid
Volumetric mass	≈ 1 kg/l
Pack	5 - 10 l cans / 1 l bottles
Shelf life	≈ 18 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +5 °C to +30 °C
Reaction time	≈ 12 hrs
Coverage when applying two coats for a fine-texture, two-coat finish	≈ 0.2 – 0.3 l/m ²

Values taken at +20 °C, 65% R.H. and no ventilation. Data may vary depending on specific conditions at the building site.

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- use at temperatures between +5 °C and +30 °C
- make sure the substrate is not frozen
- protect surfaces from direct sunlight and wind
- protect from rain and strong humidity for 24 hours following application
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in November 2020 (ref. GBR Data Report - 1220); please note that additions and/or amendments may be made over time by KERAKOLL SpA, for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com