

Legno Nat Base

Natural-effect, single component, water-based preparation coat.

To be used for base preparation in the Legno Nat cycle.



1. Easy to apply and quick to sand
2. Natural wood-effect, lightly planed
3. Compliant with Directive 2004/42/EC

Rating 3

- × VOC Low Emission
- ✓ Water Based
- ✓ Solvent ≤ 80 g/kg
- × Low Ecological Impact
- ✓ Health Care



Areas of application

- Preparation of the natural effect substrate of:
 - Legno Large, Legno Medium, Legno Small
 - traditional oak floors, brushed finish
 - pre-finished oak floors, brushed finish
 - oak floors to be repaired, brushed finish
- Specific for overcoating with Microresina Xtreme.

Do not use in external applications, generally on wooden floors other than those expressly mentioned; on wooden floors that are subject to prolonged or constant contact with water.

Instructions for use

- Preparation of substrates
 - Legno Large, Legno Medium, Legno Small: clean the floor carefully to ensure the surface is free of dust, oil, wax, silicones, residual adhesive and stains of any type. Sand with Softpad, carefully vacuum up all the dust created during sanding and then apply Legno Nat Base.
 - Floors made of oak, of traditional or pre-finished type, and to be repaired: sand the hardwood floor to obtain a smooth, clean surface that is free of dust, oil, wax, silicones, residual adhesive and stains of any type. If necessary, apply Aqua-Pur Flex to fill in any cracks and uneven areas. After ≈ 30 minutes proceed to brush, using specific equipment only. Sand with Softpad, carefully vacuum up all the dust created during sanding and then apply Legno Nat Base.

- Preparation
The product is ready-to-use. Shake well before use. Pour the product into a clean container of a suitable size. During application remix the product in the container.
- Application.
Apply Legno Nat Base evenly with Roller Plus using the coverage indicated.
After ≈ 4 hours, sand with Softpad and carefully vacuum up all the dust produced during sanding. Then proceed to apply Microresina Xtreme, following the instructions provided in the technical data sheet.
- Cleaning
Tools can be cleaned with water to remove residual traces of Legno Nat Base before the product hardens.

Special notes

- Before use acclimatize the product to reach room temperature.
- Use clean containers and tools.
- Once opened, the can must be used as quickly as possible.
- To give an even aesthetic effect, apply layers of uniform thickness and follow the recommended quantities.
- The photographic images in the catalogue and on the website, as well as the colours shown in the samples are to be considered purely indicative.
- Use material from a single production batch for each project.
- Materials from different batches may have slight colour and sheen variations.

Technical Data compliant with Kerakoll Quality Standard

Appearance	white liquid
Shelf life	≈ 12 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	2.2 l can
Temperature range for application	from +5 °C to +30 °C
Dust free	≈ 30 min.
Waiting time for overlaying with Microresina Xtreme	≈ 4 hrs after sanding down
Coverage:	
- Legno Large, Legno Medium, Legno Small	≈ 100 ml/m ²
- traditional or pre-finished oak floors	≈ 100 – 150 ml/m ²

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate and of the materials laid.

Warning

- Product for professional use
- abide by any standards and national regulations
- protect from direct sunlight and air currents for the first 3 hours
- do not use different product batches in the same room or in adjacent rooms
- if necessary, ask for the safety data sheet
- for unstable wooden types, particular substrates and for any other issues, contact the Kerakoll Worldwide Global Service 01772 456 831 – info@kerakoll.co.uk



The Rating classifications refer to the GreenBuilding Rating Manual 2012. This information was last updated in December 2023 (ref. GBR Data Report – 12.23); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.