# Proman

Hand cream. Protects against oily dirt and tough grease.

Proman creates a breathable barrier to protect the hands from oil, grease, varnishes, resins, adhesives, tar, petrol, silicon, solvents and synthetic products in general. Can be easily cleaned at the end of application with soap and water.



- 1. Dermatologically-tested
- 2. Forms a protective, breathable barrier
- 3. Easy to remove

# kerakoll

## Areas of application

→ Use

Protection of the hands from dirt and aggressive substances such as solvents, varnishes, glues, resins, adhesives, tar, petrol, silicon, oils, greases, synthetic products.

### Instructions for use

 $\rightarrow$  Application

Before starting work, evenly spread a sufficient quantity of cream on the hands without neglecting the finger nails and the areas around them. After a few minutes, the product will dry forming an thin invisible barrier on the skin that suitably protects from the substances indicated above. A greater protection can be obtained with a double application of the product. Periodically renew the application for jobs of a long duration.  $\rightarrow$  Cleaning

To remove any dirt remaining on the hands and to remove the film of barrier cream at the end of work only needs a wash with lukewarm water scrubbing forcibly with soap.

#### **Special notes**

- $\rightarrow$  Proman protective film is not sticky and does not leave prints.
- $\rightarrow$  Does not make the hands sweat.
- $\rightarrow$  It is a dermatologically tested product.

| Technical Data compliant with Kerakoll Quality Standard |  |
|---|--|
| Appearance  | white coloured paste   |
| Pack  | 500 ml tin   |
| Shelf life  | $\approx 24$ months from the date of production in original and intact packaging |
| Warning   | protect from frost, avoid direct exposure to sunlight and sources of heat        |
| рН  | neutral (7)  |
| Temperature range for application                       | from +10 °C to +30 °C  |
| Drying  | ≈ 5 mins   |
| Coverage  | $\approx 100$ applications with one pot  |

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.

#### Warning

- $\rightarrow$  Product for professional use
- $\rightarrow$  abide by any standards and national regulations
- $\rightarrow$  if necessary, ask for the safety data sheet
- → for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 globalservice@kerakoll.com



The Rating classifications refer to the GreenBuilding Rating Manual 2012. This information was last updated in April 2025; please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building site and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.

Kerakoll Spa via dell'Artigianato 9 41049 Sassuolo - MO +39 0536.816.511 info@kerakoll.com