

# Tapetex Plus

Compressible, closed-cell expanded polyethylene tape with fibre support for low-thickness perimetric joints of desolidarisation. With very low volatile organic compound emissions.

Thanks to its self-adhesive base and its integrated fibre support, Tapetex Plus guarantees excellent adhesion to the substrate; as this tape sticks to the surface to be renovated it won't leave unpleasant adhesive residues on the wall.



1. Practical and simple to apply
2. Suitable for screeds and self-levelling products
3. Highly mouldable
4. Height 50 mm

## Areas of application

### → Use

Creation perimetric joints for self-levelling products and screeds, for internal and external application.  
Desolidarisation of walls and vertical structures in general.

Do not use on loose, damp or dirty substrates.

## Instructions for use

Tapetex Plus compressible, closed-cell polyethylene tape is used for perimetric joint of desolidarisation in levelling layers and flooring. To this end, Tapetex Plus has to be laid along the whole perimeter of the area, and on the perimeter of any other vertical elements protruding from the supporting layer (such as pillars, columns, installations...).  
Remove the protective film and press the self-

adhesive part on the substrate making sure that the tape adheres perfectly to the substrate, paying particular attention to corners.  
In order to create internal corners, cut the polyethylene part without damaging the fibre support; for external corners it is recommended to cut the fibre support only in its adhesive part in order to guarantee the continuity of the polyethylene layer.

### Technical Data compliant with Kerakoll Quality Standard

Appearance	polyethylene foam roll
Colour	Green
Roll width	≈ 85 mm
Roll length	≈ 20 m
Thickness	≈ 5 mm

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate and of the materials laid.

## Warning

- Product for professional use
- abide by any standards and national regulations
- abide by any standards and national regulations
- the product is an item according to the definitions of the EC Regulation No. 1907/2006

- and therefore does not require a Safety Data Sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)



The Rating classifications refer to the GreenBuilding Rating Manual 2013. This information was last updated in September 2022; please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.