

Universal Wall Primer

Water based universal primer for walls.
Breathable. For internal and external use.
Italian design for living comfort.

Universal Wall Primer is ideal to stop superficial chalking of plasters/renders and finishing coats. Perfect to consolidate old and loose surfaces. Improves the adhesion of subsequent application cycles.



Rating 4

- × VOC Low Emission
- ✓ Water based
- ✓ Solvent ≤ 15 g/kg
- ✓ Low Ecological Impact
- ✓ Health Care

1. Stops superficial chalking of plasters/renders and finishing coats
2. Strengthens inconsistent, flaking and soft substrates
3. Reduces and regulates the water absorption on highly porous and absorbent substrates
4. Breathable. Suitable on breathable and/or dehumidifying systems
5. For internal and external use

Areas of application

- Consolidant and stabilizing primer
- Intended use:
Suitable for:
 - cement, gypsum or lime based cured, new plasters/renders and finishing coats
 - old plasters/renders and finishing coats that are still resistant and well anchored to the substrate
 - plasterboard.

Products suitable for overlaying:
- decorative paints, glazes and coverings.
Do not use
On dirty or non-cohesive substrates.
In the presence of rising damp, without suitable dehumidifying systems.

Instructions for use

- Preparation of substrates
Porous substrates with a limited level of cohesion must in any case be compact and absorbent, free from dust, oil, and grease, free from moisture rising, with no loose debris or flaky parts. The substrate must be stable, non-deformable and with no fracturing cracks. Gypsum based plasters must have a $\leq 1\%$ residual humidity measured with a calcium carbide hygrometer.
- Preparation
Universal Wall Primer is ready-to-use for wall applications as a consolidant and leveller of wall substrates and plasterboard sheets. Shake the can well before opening in order to re-disperse the product evenly. In case of particularly smooth and compact substrates, dilute the product using water by a ratio of up to 1 : 1 to make penetration easier.
- Application
Apply a uniform coat, preferably using a flat brush and crossed strokes. On highly porous substrates it is possible to apply Universal Wall Primer in more layers, wet-on-wet.
- Cleaning
Universal Wall Primer can be removed from tools and other surfaces by washing them with water before the product hardens.

Special notes

- Evaluate seasonal application conditions: different temperature and humidity conditions result in significant differences in paint drying and/or reaction times.

Certificates and marks



Technical Data compliant with Kerakoll Quality Standard

Appearance	white liquid
Specific weight	≈ 1 kg/dm ³
Shelf life	≈ 18 months from production in the original sealed packaging
Warning	protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	1 - 5 - 10 l cans
Dilution ratio	ready-to-use – max water dilution 1:1
Temperature range for application	from +5 °C to +35 °C
Waiting time for next application	≥ 4 hrs
Coverage	
- as a stabilizing agent	≈ 0.08 - 0.12 l/m ²
- as consolidant	≈ 0.15 - 0.2 l/m ²

Values taken at +20 °C, 65% R.H. and no ventilation.

Warning

- Product for professional use
- check that the substrate is perfectly clean, dry, and absorbent
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service 01772 456 831 - info@kerakoll.co.uk

The Rating classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in January 2021 (ref. GBR Data Report - 02.21); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.